

# Farb-Monitor

## FEATURES

- HIGH RESOLUTION
- PAL/NTSC SYSTEM AUTO SWITCH
- WITH Y/C AND RGB INPUT
- METAL HOUSING
- WIDE RANGE POWER SOURCE
- COMPACT DIMENSIONS



## APPLICATIONS

- VIDEO SURVEILLANCE (CCTV)
- IMAGE/DATA PROCESSING
- BROADCAST
- INDUSTRIAL, MEDICAL, OTHERS ...

## Daten

## Typ CMK-1400H

Ikegami

<b>Picture Tube:</b>	14" - 0,28 Dot Pitch
<b>Scanning Formats:</b>	<b>Dual System:</b> NTSC 525/60 ; PAL 625/50
<b>Input Signals:</b>	<b>Composite:</b> 0.5-1.0Vp-p; Neg. Sync (75 Ohm) <b>Y:</b> 1.0Vp-p w / neg. sync (75 Ohm) <b>C:</b> 0.285 Vp-p (75 Ohm) <b>RGB:</b> 0.7-1.0 Vp-p Analog (75 Ohm) <b>SYNC:</b> H+V 1.0-2.0Vp-p Neg. (75 Ohm)
<b>Output Signal:</b>	75 Ohm / High Impedance: Switchable
<b>Connections:</b>	Video In/Out : BNC x 2 <b>CVBS:</b> BNC x1 <b>RGB H + V :</b> BNC x4 <b>Y/C :</b> 4 PIN DIN
<b>Bandwidth:</b>	100Hz - 6,5 MHz (-3dB)
<b>Horizontal Resolution:</b>	650 TV Lines
<b>Linearity:</b>	Hor: 10% (Max) / Ver: 10%
<b>Operation temperature:</b>	-10 to 55 deg C
<b>Front Panel Control:</b>	Power/Sharpness/Colour/Brightness Contrast/Tint (NTSC Only)
<b>Power Source:</b>	90 - 260VAC (Auto Switch)
<b>Power Consumption:</b>	90 W
<b>Dimensions:</b>	W355 x D395 x H340mm
<b>Net/Gross Weight:</b>	16/17 kg

